

Models

- PLF8FPM delivers 8 gph of chilled drinking water when the push-button is depressed, water continues to flow as long as the button is depressed.
- PLF12FPM delivers 12 gph of chilled drinking water when the push-button is depressed; water continues to flow as long as the button is depressed.
- These models allow your facility to comply with the ADA requirements, providing the floor to nozzle height is 36" or less, and proper clear floor space is provided.

Standard Features

- Waterways Are Lead-Free In Materials & Construction
- Stainless Steel Top
- Flexible Bubbler Guard
- Heavy-Gauge Galvanized Steel Wall Mounting Sleeve
- High-Efficiency Cooling Tank and Coil
- Refrigerant R-134a
- Limited 5-Year Warranty

Installation

- Prior to roughing-in, consult with local, state, and federal codes for proper mounting height.
- Shipped with complete instructions and wall mounting sleeve.

Colors

- Standard Finish: Stainless Steel
- Optional finishes at extra cost: Regency Bronze


Accessories

Carafe/Glass Fillers (Factory Installed)


- 030239-003

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

Components in these water coolers/fountains are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.



OASIS




WATER COOLERS

FULLY-RECESSED

An installation with plenty of user headroom. Reverse side of the basin is sound dampened.

Model PLF8FPM Shown





Models covered by these specifications comply with all known Plumbing Codes. Listed by Underwriter's Laboratories. Certified by Canadian Standards Association, and Certified to Air Conditioning and refrigeration Institute Standard 1010.



Indicates conformity to European Union Directives.

Export Warranty: One year on the sealed refrigeration system and most component parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each water cooler, sample copy available upon request.

Specifications are subject to change without notice.

Copyright 1999 OASIS Corporation

Oasis® is a registered trademark of OASIS Corporation.

*Air Conditioning and Refrigeration Institute Standard Rating Condition 80°F inlet water temperature.

**Special export models available, operable on 220-240 volts, 50/60 Hz. UL, CSA and ARI certification not applicable.

Model	50°F Drinking Water 90°F Ambient Air Temperature*		Pre-Cooler	Hot 'N Cold Model	115 Volts, 60 Hz			Glass Filler Accessory Option	Cabinet Color Option	Net Weight (Approx.)
	Rated Capacity GPH	Base Rate GPH			Compr. HP	Full Load Amps	Rated Watts			
PLF8FPM**	8.0	8.0	No	No	1/5	4.6	340	Yes	Yes	92 Lbs.
PLF12FPM**	12.0	12.0	No	No	1/3	8.7	620	Yes	Yes	96 Lbs.

CLASSWATER INC.
 2600 John St., Unit 118
 Markham, ON L3R 3W3
 (905) 940-5800 Fax (905) 940-4642 888-CLASWTR(252-7987)
www.classwater.com

